

Utility Distribution Systems

Options and Accessories

10-Foot Conduit for Wiring to Hood Lights – Ease of connection to the hood light circuit. *(Standard Offering)*

12" x 12" Viewing Window in Riser – Allows user to see into the plumbing riser to view status of water temperatures and/or pressures. *(Requires special design request [SDR])*

Gas Ball Valves – Gas valves available in 1/2", 3/4", 1" and 1-1/4" diameter with shutoff ball valve at each connection along the chase. *(Selectable in CAPS®)*

Battery Backup (Uninterruptable Power Supply) – Backup for electric gas solenoid valve available for gas utilities. *(Selectable in CAPS)*

Chase Style Configuration – Optional peak top available. *(Selectable in CAPS)*

Chilled Water Line with Insulation – For use with chilled water-cooled appliances. *(Requires SDR)*

Control Packages – Save space by mounting kitchen controls in the UDS riser. Control options include Temperature Interlock, XFCC, Vari-Flow, and Melink. *(Requires SDR)*

Cord Set – Optional electric cord sets available. *(Selectable in CAPS)*

Electrical Controls – Fire fuel Shut-off (FFSO), emergency shut down, status lights, and light and fan switches available. *(Selectable in CAPS) (Vari-Flow and Melink keypads on electrical riser available by SDR)*

Fill Faucet – With 60" hose available. *(Requires SDR)*

Gas Drop Size – Alternating 3/4" and 1-1/4" thread-o-lets available as standard, placed every 12 inches and capped for future use if not being used. *(Selectable in CAPS)*

Gasketed Construction – Sealed to help protect the inside of the unit during wash down. *(Selectable in CAPS)*

Ground Fault Equipment Protection – Equipment protection for electrical branch connections available. *(Selectable in CAPS)*

Hinged Access Doors – Provides easy access into the riser without removing screws. *(Standard Offering)*

Hose Reel Assembly – Mounted on one of the plumbing risers available for auxiliary hoses. *(Requires SDR)*

Hot and Cold Water Drop Size – Both hot and cold, 3/4" and 1" diameter available, placed every 24 inches. *(Standard Offering)*

Main Gas Service Shut Off – 1-1/4", 1-1/2", and 2", mechanical or electric gas valve available on incoming service to turn gas off at the unit. *(Selectable in CAPS)*

Main Water Service Shut Off – 3/4" and 1" ball valves available on incoming service to turn water off at the unit. *(Selectable in CAPS)*

Pressure Reducing Valve – Used when the water pressure entering the UDS is too high. *(Requires SDR)*

Primary Electric Service – Choose from panel board or point-of-use: 208v main breaker with shunt trip and branch breakers available. *(Selectable in CAPS)*

Prison Package – Option available specifically for prisons/institutions to include secure construction with tamperproof screws and panels. *(Selectable in CAPS)*

Quick Disconnect Gas Hoses – Available in 48", 60", and 72" lengths, optional super-swivel available. *(Selectable in CAPS)*

Restraining Cables – Protect electrical circuits, gas, and water hoses from damage caused by pulling equipment too far away from connection points. *(Selectable in CAPS)*

Secondary Electrical Service – Choose from panel board or point-of-use: 480v main breaker with shunt trip and branch breakers available. *(Selectable in CAPS)*

Shock Arrestors – Prevent water hammering that typically occurs when the water is shut off. *(Requires SDR)*

Special Configurations – For fully custom projects contact your Greenheck representative. *(Requires SDR)*

Steam/Condensate System – For use with steam-fueled appliances. *(Requires SDR)*

Water Ball Valves – Available in 1/4" 3/8" 1/2" and 3/4" with shutoff ball valve at each connection along the chase. *(Selectable in CAPS)*

Water Filter Bracket on Chase – Allows water filter to be mounted on the chase for specific appliance applications. *(Requires SDR)*

Water Filters – Mounted inside plumbing riser for appliances requiring filtered water. Available in single appliance and multiple appliance styles. *(Selectable in CAPS)*

Water Gauges – Available for either pressure/temperature or pressure only. *(Selectable in CAPS)*

Water Hoses – Available in 48", 60", and 72" lengths. *(Selectable in CAPS)*

Weatherproof Receptacle/Switch Covers – Protects electrical outlets during wash down. *(Selectable in CAPS)*

While-in-use Receptacle Covers – Available to cover plug and receptacle while appliance is connected. *(Selectable in CAPS)*

For more information regarding Greenheck kitchen ventilation systems and components visit www.greenheck.com or consult your local Greenheck representative.

